

Brush Master Skid Loader Mower Specifications

- 1/4" H.S. Steel Housing
- 1/2" H.S. Steel Housing Sides
- Solid Steel Rear Deflector
- Heavy Duty 3 Ply Conveyor Belt Front Deflector
- 3/4" x 4" Main Reinforcing Ribs
- Retractable Front Blade Guard
- Heavy Duty Heat Treated Steel Spindle With 2-1/2" I.D. Tapered Bearings
- Super Heavy Duty Machined Steel Spindle Housing
- 1-1/4" x 8" Reinforced Steel Bar Blade Carrier
- 5/8" x 5" Free Swinging Brush Blades
- 1/2" x 4" Free Swinging Grass Blades
- 1-1/2" Grade 8 Shoulder Blade Bolts
- 6" Cutting Capacity
- Hydraulic Relief Valve
- Tree Push Bar
- Universal Lexon Door Kit
- Universal Quick Attach Plate Fits Most Skid Loaders
- Hydraulic Tips **NOT** Included
- **Requires Case Drain Line**
- Required Flow 23-43 GPM
- Blade Tip Speed :
 - SLBM-60 17,290 FPM To 17,680 FPM
 - SLBM-66 19,025 FPM To 23,350 FPM
 - SLBM-72 21,620 FPM To 26,535 FPM
- Unit Weight :
 - SLBM-60 : 1180 #
 - SLBM-66 : 1290 #
 - SLBM-72 : 1405 #