

Hydro Hatchet Skid Loader Mower



Specifications

- 3/16" H.S. Steel Housing
- 1/2" x 3" Main Reinforcing Ribs
- Solid Steel Rear Deflector
- Heavy Duty Conveyor Belting Front Deflector
- Heavy Duty Spindle With Tapered Bearings
- Heavy Duty Spindle Housing
- Motor Directly Coupled To Spindle (No Gear Box)
- Hydraulic Relief Valve
- 1/2" Thick Solid Steel Circle Blade Carrier With Hardened Blade Bolt Bushings
- 1/2" x 4" Free Swinging Blades
- 1-1/2" Grade 8 Shoulder Blade Bolts
- Universal Quick Attach Plate Fits Most Skid Loaders
- Universal Lexon Safety Door Kit
- Cutting Capacity : 2"
- Blade Tip Speed :
 - SLHH50 : 13,031 FPM To 16,288 FPM
 - SLHH60 : 15,700 FPM To 19,625 FPM
 - SLHH66 : 17,270 FPM To 21,587 FPM
 - SLHH72 : 18,840 FPM To 23,550 FPM
- Unit Weights :
 - SLHH50 : 662 #
 - SLHH60 : 767 #
 - SLHH66 : 827 #
 - SLHH72 : 887 #



1/2" Thick Solid Steel Circle Carrier With Hardened Blade Bolt Bushings