

SPECIFICATIONS FOR 19' HEAVY DUTY MID MOUNT BOOM MOWER
 (Option Codes DMP & SJC)

SPECIFICATION REQUIRED	COMPLY	EXCEPTIONS / DEVIATIONS
<u>GENERAL</u>	yes / no	
It is the purpose of the following specifications to describe a hydraulically driven boom mower. Mowing is forward and right of the right rear tire and extended by means of an articulated two section boom. This unit shall interchange with any of the following: 60" rotary brush mower head, 60" flail mower head, 60" mid mount rotary ditch mower, 72" mid mount rotary ditch mower, 60" mid mount flail ditch mower, 76" mid mount flail ditch mower. The unit shall be the manufacturer's heaviest duty model available. All deviations must be spelled out and explained in full.		
<u>MAIN RECEIVER FRAME</u>		
Main frame shall be constructed from 4" x 4" x 3/4" Structural angle fabricated into heavy duty channel receiver.		
Main frame shall be braced to rear axle on both sides.		
Main frame tractor mounts shall be of heavy duty construction, and fastened to tractor with grade 8 bolts.		
<u>BOOM MAIN FRAME</u>		
Main frame shall be constructed of 4" x 4" x 3/4" structural angle, and 4" x 4" x 3/8" structural steel tubing.		
Main frame shall connect to receiver frame with six 7/8" grade 8 bolts.		
<u>MAIN SWING POST</u>		
Main swing post shall be constructed of 6" x 6" x 3/8" structural steel tubing. (50,000 psi)		
Inner boom attachment plates shall be constructed of 3/4" thick 100,000 psi steel		
Main swing post shall be double shear design with 2" diameter 4140 chrome-molly pins.		
Main swing post shall have 2" diameter steel bushings with grease zerks for pivot.		
Swing ram shall be welded industrial type 3-1/2" diameter with 1-1/2" rod and 1" pins.		
Main swing post shall move 20* forward and 90* rearward.		
<u>INNER BOOM</u>		

Inner boom shall be constructed of 6" x 6" x 3/8" structural steel tubing with 50,000 psi tensile strength.		
Inner boom shall reinforced at all stress points with 100,000 psi tensile strength.		
Inner boom pivots shall have 1-1/2" grease able & replaceable hardened steel bushings with a Rockwell hardness of C50.		
Inner boom pivot pins shall be 1-1/2" 100,000 psi tensile strength steel case hardened to a Rockwell hardness of C50.		
Inner boom lift cylinder shall be welded industrial type 4" diameter with 2" rod and hardened steel replaceable bushings on both ends. Pins shall be 1-1/4" 100,000 psi tensile strength steel case hardened to a Rockwell hardness of C50.		
<u>OUTER BOOM</u>		
Outer boom shall be constructed of 5" x 5" x 3/8" structural steel tubing with 50,000 psi tensile strength.		
Outer boom shall be reinforced at all stress points with 100,000 psi tensile strength steel.		
Outer boom pivots shall have 1-1/2" grease able & replaceable hardened steel bushings with a Rockwell hardness of C50.		
Outer boom Pivot pins shall be 1-1/2" 100,000 psi tensile strength steel case hardened to a Rockwell hardness of C50.		
Dipper cylinder shall be welded industrial type 4" diameter with 2" rod and hardened steel replaceable bushing on rod end. Rod end pin shall be 1-1/4" 100,000 psi tensile strength steel case hardened to a Rockwell hardness of C50. Base pin shall be 1-1/4" Chrome molly steel..		
Deck roll cylinder shall be welded industrial type 3-1/2" diameter with 1-1/2" rod and hardened steel replaceable bushing on rod end. Pins shall be 1" grade 5 bolts.		
<u>REACH</u>		
Mower shall reach 15'-4" up / 9'-6" down / 19' out		
Reach is measured from center line of tractor and may vary depending on model of tractor or tire size.		
<u>HYDRAULICS</u>		
Reservoir shall be 65 gallon walk over style and equipped with in tank filter rated at 75 G.P.M., 10 micron element. Tank shall have shut off valve at suction line.		

Pump shall be front mounted tandem steel gear type with heavy duty drive line.		
Pump shall be 37 G.P.M. @ 2,200 R.P.M. @ 2,500 P.S.I. for mower drive and 10 G.P.M. @ 2,200 R.P.M. @ 2500 P.S.I. For control valve.		
Suction Hose shall be 2" inside diameter. Pressure hose shall be 1" diameter rubber hose rated at 3000 P.S.I. working pressure.		
All hydraulic fittings shall o-ring / JIC type fittings.		
<u>MOWER VALVE</u>		
Mower on / off valve shall be electric controlled with hydraulic brake feature for shut down, & starter lock out.		
Boom control valve shall be ECU controlled cartridge style with single joystick control.		
<u>CUTTER HEAD</u>		
Shall be 60" (actual) cutting width.		
Cutter head bonnet shall be 10 gauge steel. End plates shall be 3/8" thick steel.		
Cutter head back angle shall be formed 1/4" HS steel. Front cutter head cross tube shall be 2" x 2" x 1/4" structural steel tubing.		
Cutter head shall have skid runners.		
Cutters head shall have heavy duty rubber conveyor belting rear debris deflector.		
Hydraulic motor drive shall be machined housing with tapered bearings. Motor shall drive rotor with double banded v belt.		
Rotor shaft shall be constructed of 4-1/2" OD x 3/8" wall DOM steel tubing.		
Rotor shaft bearings shall be 2-3/16" ID self aligning cartridge flange style.		
Rear roller shall be 6" OD with 1-1/4" replaceable shaft. It shall be adjustable from 0" to 6" cutting height.		
Hydraulic motor shall be heavy duty steel gear type .		
<u>COUNTER WEIGHT</u>		
Shall be 1800 lbs. Frame mounted . (mounted under oil tank)		