

McKenzie Three Point Ditch Bank Flail Mower



(Model TPDMGM76 Shown)

Specifications:

- Available Cutting Widths: 60" / 76".
- Cutting Capacity: Std Knife Grass / Heavy Duty Knife 1" Brush.
- Cutter Shaft 4-1/2" O.D. 3/8" Wall Tubing.
- Cutter Shaft Speed 2100 R.P.M.
- Cutter Shaft Bearings 2-3/16" I.D.
- Cutter Head Bonnet 10 Gauge Steel.
- 1/4" Formed Rear Frame.
- Cutter Head End Plates 3/8" Thick.
- 6" Diameter Rear Roller With 1-1/4" Bearings.
- Cutter Head Rotation 90* Up / 50* Down.
- Hydraulic Driven Cutter Head At 37 G.P.M. @ 2500 PSI
- PTO Driven Hydraulic Pump With Speed Incomer .
- Category 5 Drive Line.
- 5" x 5" x 3/8" Tubing Main Frame.
- Deck Rotation Ram 3-1/2" Diameter With 1-1/2" Diameter Rod.
- 65 Gallon Oil Reservoir With In Tank Filter.



McKenzie Supply & Equipment Ltd.
715-234-6848
WWW.MCKENZIELTD.COM