

## Three Point Wood Chuck Boom Mower Specifications

- 4" x 4" x .375" Tubing Main Frame
- 3" x 3" x .25" Tubing Three Point
- 6" x 6" x .375" Tubing Swing Post
- 6" x 6" x .25" Tubing Inner Boom
- 5" x 5" x .25" Tubing Outer Boom
- 1.5" Case Hardened Steel Pivot Pins
- 4" x 30" x 2" Rod Main Lift Cylinder ( 21' )
- 4" x 24" x 2" Rod Main Lift Cylinder ( 19' )
- 4" x 20" x 2" Rod Main Lift Cylinder ( 17' )
- 4" x 24" x 2" Rod Crowd Cylinder
- 3.5" x 20" x 1.5" Rod Swing Cylinder
- 3.5" x 14" x 1.5" Rod Deck Roll Cylinder
- All Cylinders Are Welded Industrial Style
- 60" Hydraulic Drive Rotary Head Mower
- .1875" Thick Grade 50 Steel Housing
- .75" x 28" Diameter Circle Blade Carrier With Harden Steel Blade Bolt Bushings
- Heat Treated Steel Spindle With 2-3/8" I.D. Tapered Bearings
- Heavy Duty Machined Cast Steel Hub
- Heavy Duty Steel Gear Hydraulic Drive Motor
- Mower Mounted Speed Increaser For PTO Drive Hydraulic Pump With Category 5 Drive Line
- 37 GPM Steel Gear Pump @ 2500 PSI
- Full Flow Hydraulic Relief Valve For Mower Drive
- 1" Mower Lines Rated @ 3000 PSI
- .375" Boom Lines Rated @ 3000 PSI
- 65 Gallon Steel Oil Reservoir
- 75 GPM In Tank Return Line Filter With Gauge
- Category II Three Point Mount
- Available Reaches 17' / 19' / 21' Measured From Center Line Of Tractor
- Cutting Capacity 4"
- **Requires Four Tractor Remotes**