

Three Point Wood Chuck Ditch Mower Specifications

- 4" x 4" x .25" Tubing Mount Frame
- 5" x 5" x .375" Tubing Main Arm
- 3" x 3" x .25" Tubing Third Point
- 1.5" Case Hardened Steel Pivot Pin
- 1.5" I.D. Replaceable Hardened Steel Pivot Bushings
- 3.5" x 14" x 1.5" Rod Deck Roll Cylinder
- Hydraulic Driven Rotary Head Mower
- .1875" Thick Grade 50 Steel Housing
- .75" x 28" Diameter Circle Blade Carrier With Hardened Blade Bolt Bushings
- Heat Treated Steel Spindle With 2-3/8" I.D. Tapered Bearings
- Heavy Duty Machined Cast Steel Hub
- Heavy Duty Steel Gear Hydraulic Drive Motor
- Mower Mounted Speed Increaser For PTO Drive Hydraulic Pump With Category 5 Drive Line
- 37 GPM Steel Gear Pump @ 2500 PSI
- Full Flow Hydraulic Relief Valve For Mower Drive
- 1" Mower Lines Rated @ 3000 PSI
- .375" Deck Roll Line Rated @ 3000 PSI
- 65 Gallon Steel Hydraulic Oil Reservoir
- 75 GPM In Tank Return Line Filter With Gauge
- Category II Three Point Hitch
- Available Cutting Widths 60" / 66" / 72"
- Cutting Capacity 4"
- **Requires One Tractor Remote**