

Tree Master Skid Loader Brush Cutter



Specifications

- 3/4" Thick End Plates
- 1/4" H.S. Steel Cutter Head Bonnet
- 6" x 4" x 3/8" Rear Tube Frame
- 3" x 3" x 1/4" Front Tube Frame
- 1/4" Thick Rear Solid Steel Deflector
- 8" Cutting Capacity
- 3" Cutter Shaft Bearing With Anti-Wrap Protection
- 8" x 8" x 1/2" Square Tubing Rotor
- 1600-1800 RPM Cutter Shaft
- 18" Knife Cutting Diameter
- S7 Tool Steel Rigid Knives Heat Treated To RC60
- Spring Tightened Triple Banded V Belt Drive
- Steel Gear Hydraulic Motor With Relief Valve
- Machined Spindle Drive Housing With Tapered Bearings
- Adjustable Tree Push Bar
- 1-3 Inch Adjustable Skid Shoes With 3/4" Thick Replaceable Wear Runners
- Universal Quick Attach Plate Fits Most Skid Loaders
- Lexon Safety Door Kit
- Hydraulic Tips **NOT** Included
- **Requires Case Drain Line**
- Unit Weight :
 - SLTM-64 : 2250 #
 - SLTM-72 : 2395 #

Sold By :

McKenzie Supply & Equipment Ltd.
1660 20-1/2 Street
Rice Lake WI 54868
Phone # 715-234-6848
www.mckenzieltd.com

