

## TV145 Mounted Brush Master Boom Mower



- 6" x 4" x .25" Tubing Loader Mount
- 3" x 3" x .25" Tubing Loader Mount Bracing
- 4" x 4" x .375" Tubing Main Frame
- 6" x 6" x .375" Tubing Swing Post
- 6" x 6" x .375" Tubing Inner Boom
- 5" x 5" x .25" Tubing Outer Boom
- 1.5" Case Hardened Steel Pivot Pins
- 1.5" I.D. Replaceable Hardened Steel Pivot Bushings
- 4" x 30" x 2" Rod Main Lift Cylinder ( 21' & 23' )
- 4" x 24" x 2" Rod Main Lift Cylinder ( 19' )
- 4" x 24" x 2" Rod Crowd Cylinder
- 3.5" x 20" x 1.5" Rod Swing Cylinder
- 3.5" x 14" x 1.5" Rod Deck Roll Cylinder
- All Cylinders Are Welded Industrial Style With Replaceable Hardened Steel Bushings
- 60" Hydraulic Drive Rotary Head Mower
- .1875" Thick Grade 50 Steel Housing With .375" Thick Sides
- 1.25" x 8" Reinforced Bar Blade Carrier ( Disk Carrier Optional )
- 4.5" x 12" 4140 Chrome Molly Steel Spindle With 2-1/2" I.D. Tapered Bearings
- Heavy Duty Machined Steel Hub
- Heavy Duty Steel Gear Drive Motor
- Mower Mounted Speed Increaser For PTO Drive
- Hydraulic Pump With Category 5 Drive Line
- 37 GPM Steel Gear Hydraulic Pump @ 2500 PSI
- Full Flow Hydraulic Relief Valve For Mower Drive
- Fully Proportional Electronic Boom Control Valve With Single Joy Stick Control.
- 1" Mower Lines Rated @ 3000 PSI
- .375" Boom Lines Rated @ 3000 PSI
- 65 Gallon Steel Oil Reservoir
- 75 GPM In Tank Return Line Filter With Gauge
- Mounts In Place Of Tractor Loader
- Available Reaches 19' / 21' / 23' Measured From Center Line Of Tractor
- Cutting Capacity 5"

Sold By :