

2008 New Wood Chuck Skid Loader Mower



Model SLWC6636 Shown

Specifications

- 1/4" H.S. Steel Housing
- 3/4" x 3" Main Reinforcing Ribs
- Solid Steel Rear Deflector
- Heavy Duty Conveyor Belting Front Deflector
- Heavy Duty Spindle With 2-3/8" I.D. Tapered Bearings
- Heavy Duty Spindle Housing
- Motor Directly Coupled To Spindle (No Gear Box)
- Hydraulic Relief Valve
- 3/4" Thick Solid Steel Circle Blade Carrier With Hardened Steel Blade Bolt Bushings
- 1/2" x 4" Free Swinging Blades
- 1-1/2" Grade 8 Shoulder Blade Bolt
- Universal Quick Attach Plate Fits Most Skid Loaders
- Universal Lexon Safety Door Kit
- Cutting Capacity : 4"
- Blade Tip Speed :
 - SLWC60 : 15,700 FPM To 19,625 FPM
 - SLWC66 : 17,270 FPM To 21,587 FPM
 - SLWC72 : 18,840 FPM To 23,550 FPM
 - SLWC78 : 20,410 FPM To 25,512 FPM
- Unit Weights :
 - SLWC60 : 1050 #
 - SLWC66 : 1135 #
 - SLWC72 : 1269 #
 - SLWC78 : 1367 #



3/4" Thick Solid Steel Circle Carrier With Hardened Blade Bolt Bushings

